

# TAKSTAR® 得胜



## XR-1016FX / XR-1824FX 模拟调音台 | ANALOG MIXER

使用手册 | USER MANUAL

## ■ PREFACE

Dear Customer,

Thank you for purchasing Takstar XR-1016FX/XR-1824FX Analog Mixer. In order to better understand and use the product, please read this manual carefully.

If you have any questions or suggestions, please contact our local dealer.

## ■ FEATURES

- Robust metal housing
- Professional DSP effector with 16 effects available
- 10/18CH XLR mic inputs, 4CH bus outputs, 6CH with built-in compressor; separate stereo pan control on each channel
- Two stereo channels capable of direct routing to L/R
- Bluetooth & USB-A MP3 playback, stereo USB-B audio input & output
- Low-noise preamp + 48V phantom power
- 3-band equalizer on each channel for treble/mid-range/bass adjustment
- Studio quality headphone output
- 60mm high precision faders

## ■ APPLICATIONS

Commercial performances, large gatherings, outdoors

## ■ PACKING LIST

Analog Mixer.....	1
User Manual.....	1
Power Cord.....	1

## ■ SPECIFICATIONS

### MONO INPUT

MIC IN: 10/18CH Bal XLR  
Frequency Response: 20 Hz - 20 kHz, +/-1 dB  
Distortion (THD+N): <0.003% at +0 dB, 20 Hz-20 kHz  
Sensitivity: 0 dB to -50 dB  
Max Input Level: +20 dBu  
MIC IN Impedance: 14 k $\Omega$ , unbal  
Phantom Power: +48V  
Low Cut: 80 Hz

LINE IN: 8/16CH Bal TRS  
Frequency Response: 20 Hz - 20 kHz, +/-1 dB  
Distortion (THD+N): <0.003% at +0 dB, 20 Hz-20 kHz  
Sensitivity: 20 dB to -30 dB  
Max Input Level: +40 dBu  
LINE IN Impedance: 21 k $\Omega$ , unbal

### STEREO INPUT

LINE IN: 4 pairs of Bal TRS + 2 pairs of Unbal RCA  
Frequency Response: 20 Hz - 20 kHz, +/-1 dB  
Distortion (THD+N): <0.003% at +0 dB, 20 Hz-20 kHz  
Sensitivity: 20 dB to -30 dB  
LINE IN Impedance: 15 k $\Omega$ , unbal

### MONO EQ

HIGH: +/-15 dB @ 10 kHz Shelving  
MID: +/-15 dB @ Freq.sel. from 100Hz to 8kHz  
-Bell  
LOW: +/-15 dB @ 100 Hz Shelving

### DSP

DSP: 20/27 bit digital signal  
A/D & D/A Converter: 24 bit  
FX Type: 4 algorithms: reverb, chorus, delay, flanger - 16 presets  
Foot Switch: TS jack (for effect return mute and unmute)

### STEREO EQ

HIGH: +/-15 dB @ 10 kHz Shelving  
MID: +/-15 dB @ 1,250 kHz Bell  
LOW: +/-15 dB @ 100 Hz Shelving

### OUTPUT

MAIN OUTPUT: 1 pair of XLR + 1 pair of 6.3mm TRS  
MAIN Max Output Level: +28 dBu  
AUX OUTPUT: 4 TRS  
AUX Max Output Level: +28 dBu  
STEREO GROUP 1/2 OUTPUT: 2 TRS  
GROUP Max Output Level: +28 dBu  
STEREO GROUP 3/4 OUTPUT: 2 TRS  
GROUP Max Output Level: +28 dBu  
Monitor Output: 1 pair of TRS  
Stereo Headphone Output: 1 Stereo TRS


### POWER SUPPLY

Main Input Voltage: 100 V - 240 V AC, 50-60 Hz  
Power Consumption: 30W


XR-1016FX Dimensions: 468\*440\*95 mm; Weight: 6.6 kg  
XR-1824FX Dimensions: 680\*450\*95 mm; Weight: 9.3 kg

## ■ DESCRIPTIONS

### XR-1016FX REAR PANEL




### XR-1824FX REAR PANEL



- ① **AC INPUT**  
Connect the power cord to this socket and properly connect it to a 220V grounded AC power source.
- ② **POWER SWITCH**  
Turns the mixer power on or off.
- ③ **USB-B CONNECTOR**  
Connect a computer to this port via a UBS cable for stereo recording and playback of audio signals.
- ④ **USB-A STORAGE CONNECTOR**  
Connect a USB flash drive for music playback and recording.
- ⑤ **AUX OUTPUTS 1 – 4**  
These AUX outputs feature 1/4" TRS balanced jacks and provide signal from auxiliary outputs. The output level is controlled by the AUX Level control (10).
- ⑥ **BUS OUTPUTS 1 – 4**  
These BUS outputs feature 1/4" TRS balanced jacks and provide signal from group outputs. The output level is controlled by the BUS Level fader.

## MONO INPUT

- 1 MIC IN  
This XLR balanced mic preamp input supports sources with a gain range of 0 dB to -50 dB. All MIC/LINE inputs feature an 80 Hz high pass filter, which can be enabled to reduce low frequency pops, bumping and rattling noise when using a mic for vocals.
- 2 LINE IN (1/4)  
These jacks are 1/4" balanced (TRS) high impedance inputs. The cores are positive and used for unbalanced inputs. MIC IN and LINE IN should not be used at the same time.
- 3 GAIN  
May refer to MIC GAIN or LINE GAIN subject to input source. Using MIC IN, Gain Range: 0~50dB; Using LINE IN, Gain Range: -20~+30dB. Preferably set to a level where PEAK LED only flashes occasionally, so to prevent distortion.
- 4 LOW CUT  
An 80Hz low cut filter toggle. Enable it to cut off unwanted low frequency noise (e.g., operating noise, stage noise, air noise) to improve clarity. These unwanted energy could drain power from your audio system.
- 5 COMP  
Turning this knob clockwise lowers the compressor threshold, increasing the amount of compression. The compression ratio is within 4:1 and varies with the signal level and the amount of compression. This is useful for controlling peak levels from live sources, and is designed to subtly tame the level of live vocals without noticeable artifacts.
- 6 HIGH EQ  
This smooth-tilt tone control adjusts treble frequency levels ( $\pm 15$ dB at 10 kHz), reducing noise or boosting brightness.
- 7 MID EQ  
The IF control is set to 1250 Hz, with a gain of +/-15 dB and a bell curve.
- 8 MID FREQ  
This control knob determines the center frequency of the MID EQ control. The center frequency of the bandpass filter can be set between 100 Hz and 8kHz.
- 9 LOW EQ  
This smooth-tilt tone control adjusts the bass frequency level ( $\pm 15$  dB at 100 Hz), adding depth to thin sounds or clarity to overly thick sounds.
- 10 AUX1-4  
Each channel of the XR-1016FX mixer provides 4 aux sends; AUX1 and AUX2 are PRE fader sends. AUX3 is a POST or PRE fader send, depending on the position of the AUX3 PRE/POST button (32). FX/AUX4 send is always post-fader. FX/AUX4 is sent to the internal PRO DSP FX board. Signals in FX/AUX4 send are also routed to the AUX4 OUTPUT jack on the rear panel.
- 11 PAN  
This control determines the signal position of the assigned L/R channel and group 1/2 bus. Turning the knob counterclockwise increases the amount of signal sent to the left channel and odd group; while turning it clockwise increases the amount of signal sent to the right channel and even group.  
For example, when the GROUP SWITCH (17) is in the 1/2 position, turning the knob counter-clockwise will increase the amount of signal sent to Group 1, and turning it clockwise will increase the amount sent to Group 2. Equal amount is sent to each group if rotated to the middle.



# XR-1016FX/XR-1824FX ANALOG MIXER

## 12 MUTE SWITCH

Pressing this switch will mute the signal sent to the main mix, aux sends, and FX effects. The mute switch does not affect the signal sent to the solo system.

## 13 MUTE LED

The mute button is equipped with a red LED that lights up when the channel is muted.

## 14 PEAK LED

This LED usually indicates that the channel signal level is approaching clipping (distortion), but it also lights up when muted. Because the peak indicator circuit monitors the signal after gain, EQ and master level, peaks can be caused by high settings of any of these controls. It lights up upon a static signal (test sound) of +15 dBu, which corresponds to the audible peak of a highly dynamic signal (i.e. a piano). When lit, there is about 5dB of headroom remaining, and the gain and EQ boost should be reduced. Under optimal settings of input gain and EQ, LED will only flash briefly at the loudest peak.

## 15 PFL SWITCH

This PFL button allows monitoring of the signal on this channel through a speaker connected to the CTRL ROOM OUTPUT or a headphone connected to the PHONES OUTPUT.

## 16 MAIN SWITCH

This button allows signals to be routed individually to the MAIN MIX.

## 17 GROUP 1-4 SWITCH


The BUS1/2, BUS3/4 buttons allow the signal to be routed to the stereo BUS 1/2, 3/4 respectively.

## 18 CHANNEL FADER

Used to adjust the signal level of the channel sent to the main output; control range is  $-\infty$  to +10dB, the optimal position is 0dB.

## 19 LINE/Hi-Z SWITCH

To connect a guitar directly to the mixer without using a DI Box, press this switch down first; then connect the guitar's output to the channel's 1/4" TRS input. This helps to match the directly connected input impedance and preserve high frequency fidelity. The channel's 1/4" TRS input will become a line input, just like any other mono line input. To use guitars or other instruments on other channels, you'll need to use an external DI box first. Without the DI box or if this switch is not pressed the guitar may sound dull and muddy.



## STEREO INPUT

### 20 STEREO INPUTS (RCA)

RCA L/R line input which accepts signal from MP3 or CD player.

### 21 STEREO INPUTS


1/4" TRS balanced or 1/4" TS unbalanced line inputs. If you are connecting a mono source, use the left (mono) input and the mono signal will appear on both sides of the main mix.

### 22 STEREO GAIN

This control establishes the nominal operating level of the channel. The input gain can be adjusted in a wide range (-20—+30dB). To maximize the signal-to-noise ratio, the gain should be set to an appropriate level. To do so, set the channel fader to 0, then press the PFL switch and observe the LEVEL LED. If the CLIP LED glows and stays red, you need to reduce the gain.


### 23 LINE IN / USB-B IN SWITCH

When this switch is not pressed, the input signal of this channel is provided by line input; or when pressed, provided by USB-B.




PANEL

- 24 FOOT SWITCH  
This 1/4" TRS connector is where the foot switch is connected. The internal effect can be turned on and off through the foot switch. If the internal effect channel has been muted, the foot switch will not work.
- 25 PHONES OUTPUT  
This 1/4" TRS connector provides stereo headphone output. The output volume of this channel is controlled by the PHONES volume control knob.
- 26 L/R MAIN OUTPUT  
There are two 1/4" TRS balanced jacks and two balanced XLR outputs for Left/Right outputs. 1/4" output can be connected with Tip, Ring, Sleeve (TRS) balanced or Tip, Sleeve (TS) unbalanced connector. Its output level is controlled by MAIN FADER (39). Both XLR and TRS outputs can be used at the same time.
- 27 CTRL ROOM OUTPUT  
These 1/4" jacks are usually connected to the input amplifier or headphone amplifier in the control room.
- 28 PHANTOM POWER (two on XR-1824FX)  
This switch applies +48VDC to the XLR input connector to power mics that require phantom power. If enabled, do not connect unbalanced dynamic mics or other XLR input devices that cannot handle this voltage.
- 29 FX TO AUX 1-3  
This allows routing of signal in the FX return channel to AUX1-3 send.
- 30 AUX3 PRE/POST  
This button sets whether the AUX3/FX signal is pre-fader or post-fader.
- 31 AUX 1-4 MASTER  
These potentiometers control the AUX1-4 master level. When PFL button is pressed, the signal present on the respective individual aux output can be monitored through the speaker connected to the CTRL ROOM OUTPUT (27) or the headphones connected to the PHONES OUTPUT (25).
- 32 LEVEL LED  
This 12-LED level meter helps to control the main mix output level. Keep the output level below the "CLIP" LED to avoid signal overload and distortion.
- 33 PFL ACTIVE LED  
This LED illuminates when one or more of the PFL buttons are pressed.
- 34 CTRL ROOM VOLUME  
This is the level control of signal routed to the CTRL ROOM OUTPUT. During regular use, the main channel mix signal is routed to this output; when one or more PFL buttons are pressed, the PFL bus signal is routed to CTRL ROOM OUTPUT and PHONES OUTPUT.
- 35 PHONES VOLUME  
This knob controls the level of the headphone output. Set the headphone volume level to the minimum (-∞) before connecting and wearing headphones to avoid hearing damage.



**36 MONITOR SETTINGS**  
 There are two buttons for monitoring settings. For the upper button: when not pressed, it monitors the audio from MAIN L/R; when pressed, it monitors audio from BUSSES. For the lower button: when not pressed, it monitors audio from BUS 1/2; when pressed, it monitors audio from BUS 3/4.

**37 FX FADER**  
 This fader controls the signal level from the internal DSP effector. The mute button, when pressed, disables signal flow to the output bus or main mix. The PFL button allows the current channel's signal to be monitored by CTRL ROOM OUTPUT and PHONES OUTPUT. The MAIN button allows the effect signal to be sent to the main channel for mixing. The 1/2, 3/4 buttons allow the effect signal to be sent to the stereo busses BUS 1/2 or BUS 3/4.



**38 BUS 1/2, BUS 3/4 FADER**  
 Faders BUS1/2 and BUS3/4 control the level of the stereo bus outputs. BUS 1/2 and BUS 3/4 can be fed by each input channel to create stereo audio groups routed to the physical BUS OUTPUTS. When the MUTE button is pressed, signal flow to the BUS output or main mix is disabled. The MAIN button next to the BUS fader routes the BUS to the MAIN MIX. When the PFL button is pressed, the signal present in the BUS can be monitored through speaker connected to CTRL ROOM OUTPUT or headphones connected to PHONES OUTPUT.

**39 MAIN FADER**  
 This fader controls the level of the MAIN MIX.

**40 PREVIOUS TRACK**

**41 PAUSE/PLAY**

**42 NEXT TRACK**


**43 BLUETOOTH (BT) MODE LED**

**44 USB-A PLAYBACK MODE LED**

**45 USB REC MODE LED**

**46 EFFECTS SELECTION (1-16) KNOB & MODE SELECTION BUTTON**


**47 EFFECT STATUS (1-16) DISPLAY**



## OPERATIONS


a. BT MODE (see picture on the right)

After power on, the BT indicator will flash for 2 minutes, awaiting Bluetooth connection. Search for "Mixer BT" on your Bluetooth device and connect. Once paired successful, the BT indicator will stay lit. You can then manually play media inside your device using PAUSE/PLAY/PREVIOUS TRACK/NEXT TRACK. If without Bluetooth connection within 2 minutes, the Bluetooth function automatically shuts down and the BT indicator turns off. To re-try Bluetooth connection, press and hold the MODE button for 3 seconds to activate Bluetooth pairing and establish connection.



b. USB MODE (see picture on the right)


When a USB drive is inserted via USB-A port, press the MODE button to switch to USB playback mode. In this case, the USB indicator will light up, and you can play media inside your USB drive using PAUSE/PLAY/PREVIOUS TRACK/NEXT TRACK. Note: You cannot switch to USB playback mode by pressing the MODE button if no USB drive is inserted via USB-A.



# XR-1016FX/XR-1824FX ANALOG MIXER


## c. REC MODE (see picture on the right)

While a USB drive is inserted via USB-A and mixer under USB playback mode (i.e., green USB indicator glows), press and hold MODE button for 3 seconds to enter REC mode. In this case, the REC indicator flashes red while recording normally. Press and hold MODE button for 3 seconds again to pause recording (REC indicator glows solid red). Again, press and hold MODE button for 3 seconds to exit REC mode and start playback of the recorded file.



## d. REC PLAYBACK MODE (see picture on the right)

While playing the recording file, the USB green light and the REC red light will be on at the same time, and you can control the playback using PAUSE/PLAY/PREVIOUS TRACK/NEXT TRACK audio file. Press and hold the MODE button again for 3 seconds to continue recording. During the recording process, press and hold the MODE button for 3 seconds to pause recording. While paused, press the MODE button once to return to Bluetooth mode, and start new operation or selection.






## DSP Effector

Both XR-1016FX and XR-1824FX are equipped with an internal PRO DSP FX board with 16 FX presets. Rotate the EFFECTS KNOB to select among the 16 sound effects:

- |                 |                    |                   |                    |
|-----------------|--------------------|-------------------|--------------------|
| 01. SMALL HALL  | 05. THIN PLATE     | 09. ANALOG DELAY  | 13. PHASER         |
| 02. LARGE HALL  | 06. PLATE          | 10. CHORUS VERB   | 14. GATED REVERB   |
| 03. SMALL ROOM  | 07. SPRING REVERB  | 11. STEREO CHORUS | 15. FLANGER REVERB |
| 04. BRIGHT ROOM | 08. MULTITAP DELAY | 12. FLANGER       | 16. VOCAL ECHO     |


Enrich your audio with any of the above preset effects.

## PLUG PINOUT DIAGRAM




### XLR Connector


- Bal XLR Wiring:  
1 = Shield (Ground)  
2 = Positive (+/Hot)  
3 = Negative (-/Cold)



# XR-1016FX BLOCK DIAGRAM



XR-1824FX BLOCK DIAGRAM



## ■ CAUTIONS

To avoid electric shock, overheat, fire, radiation, explosion, mechanical risk and injury or property loss due to improper use, please read and observe the following items before use:

1. Please check if the power of the connected equipment matches with that of this product before operation. Adjust the volume to proper level during operation. Do not operate at over-power or high-volume level for extended time to avoid product malfunction or hearing impairment.
2. If there is any abnormality during use (e.g., smoke, strange odor), please kill the power switch and unplug from power source, then send the product to the dealer for repair.
3. Keep this product and its accessories in a dry and ventilated area. Do not store in a humid or dusty area for extended time. Keep away from fire, rain, liquid intrusion, bumping, throwing, vibrating, or from blocking any ventilation openings, to prevent malfunction.
4. The product must, when installed on walls or ceilings, be fixed firmly in place at adequate strength to prevent from falling.
5. Please abide by safety rules during operation. Do not use the product in places prohibited by laws or regulations to avoid accident.
6. Do not disassemble or repair the product by yourself to avoid injury. If you have any questions or require any services, please contact our local dealer.



扫一扫，了解更多产品  
Scan for more  
product information

## **广东省电声工程技术研究开发中心 广东得胜电子有限公司制造**

地址：广东省惠州市博罗县龙溪街道富康一路2号

服务热线：400 6828 333 传真：0752 6383950

邮箱：xs@takstar.com

网址：www.takstar.com

Guangdong Takstar Electronic Co., Ltd.

Address: No. 2 Fu Kang Yi Rd., Longxi Boluo

Huizhou, Guangdong 516121 China

Tel: 86 752 6383644 Fax: 86 752 6383952

Email: sales@takstar.com

Website: www.takstar.com